

**DuPont™ StoneTech® Professional Enhancer**

Version 2.0

Revision Date 08/31/2010

Ref. 130000031663

This SDS adheres to the standards and regulatory requirements of the United States and may not meet the regulatory requirements in other countries.

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product name : DuPont™ StoneTech® Professional Enhancer
MSDS Number : 130000031663

Manufacturer : DuPont
1007 Market Street
Wilmington, DE 19898

Product Information : 1-800-441-7515 (outside the U.S. 1-302-774-1000)
Medical Emergency : 1-800-441-3637 (outside the U.S. 1-302-774-1139)
Transport Emergency : CHEMTREC: 1-800-424-9300 (outside the U.S. 1-703-527-3887)

SECTION 2. HAZARDS IDENTIFICATION

Potential Health Effects

Skin : May cause skin irritation.

Eyes : May cause eye irritation. tearing, Blurred vision.

Inhalation : Inhalation of decomposition products in high concentration may cause shortness of breath (lung oedema). Inhalation of aerosol or fine spray mist may cause serious respiratory problems., Effects of breathing high concentrations of vapour may include:, dizziness, confusion, incoordination, drowsiness, or unconsciousness.

Ingestion
2-Butoxyethanol : Red blood cell destruction which could produce tiredness, rapid heartbeat, dizziness, pale skin, leg cramps, shortness of breath, jaundice (yellow tinge to skin and eyes)

Target Organs
2-Butoxyethanol : Blood

Carcinogenicity

None of the components present in this material at concentrations equal to or greater than 0.1% are listed by IARC, NTP, or OSHA, as a carcinogen.


DuPont™ StoneTech® Professional Enhancer

Version 2.0

Revision Date 08/31/2010

Ref. 130000031663

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Component	CAS-No.	Concentration
Water	7732-18-5	81 - 95 %
Modified Linseed Oil		5 - 15 %
2-Butoxyethanol	111-76-2	<2 %
Fluorinated Acrylic Copolymer		<2 %

SECTION 4. FIRST AID MEASURES

- Skin contact : Wash off immediately with soap and plenty of water. Wash contaminated clothing before re-use.
- Eye contact : Rinse immediately with plenty of water for at least 15 minutes. Seek medical advice.
- Inhalation : Move to fresh air. Oxygen or artificial respiration if needed. Symptoms may be delayed. Call a physician immediately.
- Ingestion : Call a physician or poison control centre immediately. If swallowed, DO NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person.
- General advice : When symptoms persist or in all cases of doubt seek medical advice.

SECTION 5. FIRE-FIGHTING MEASURES

Flammable Properties



DuPont™ StoneTech® Professional Enhancer

Version 2.0

Revision Date 08/31/2010

Ref. 130000031663

- Flash point : > 110 °C (> 230 °F)
- Thermal decomposition : > 200 °C (> 392 °F)
To avoid thermal decomposition, do not overheat.
Thermal decomposition can lead to release of irritating gases and vapours.
- Fire and Explosion Hazard : The product itself does not burn. Hazardous decomposition products formed under fire conditions. Hazardous combustion products: Hydrogen fluoride Carbon dioxide (CO2) Carbon monoxide Other hazardous decomposition products may be formed.
- Suitable extinguishing media : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
- Firefighting Instructions : Wear self contained breathing apparatus for fire fighting if necessary. Evacuate personnel to safe areas. Do not allow run-off from fire fighting to enter drains or water courses.

SECTION 6. ACCIDENTAL RELEASE MEASURES

NOTE: Review FIRE FIGHTING MEASURES and HANDLING (PERSONNEL) sections before proceeding with clean-up. Use appropriate PERSONAL PROTECTIVE EQUIPMENT during clean-up.

- Safeguards (Personnel) : Evacuate personnel to safe areas. Use personal protective equipment. Ventilate the area.
- Spill Cleanup : Dam up. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Pick up and transfer to properly labelled containers.
- Accidental Release Measures : Do not discharge to streams, ponds, lakes or sewers. Avoid subsoil penetration.

SECTION 7. HANDLING AND STORAGE

- Handling (Personnel) : Avoid formation of respirable particles. Do not breathe vapor or mist. Avoid contact with skin, eyes and clothing.
Wash hands before breaks and immediately after handling the product. Wash



DuPont™ StoneTech® Professional Enhancer

Version 2.0

Revision Date 08/31/2010

Ref. 130000031663

contaminated clothing before re-use.

Handling (Physical Aspects) : To avoid thermal decomposition, do not overheat. Thermal decomposition can lead to release of irritating gases and vapours. Do not spray near open flame or heated surface.

Storage : Keep tightly closed in a dry, cool and well-ventilated place.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Engineering controls : Use only in area provided with appropriate exhaust ventilation. Use an airless flow type of spray applicator. Keep spraying pressure below 60 psi.

Personal protective equipment
Respiratory protection : In case of mist, spray or aerosol exposure wear suitable personal respiratory protection and protective suit.

Hand protection : Additional protection: Impervious gloves

Eye protection : Wear safety glasses or coverall chemical splash goggles.

Skin and body protection : Lightweight protective clothing

Exposure Guidelines
Exposure Limit Values
 2-Butoxyethanol

PEL: (OSHA) 50 ppm 240 mg/m³ 8 hr. TWA
 Skin designation

TLV (ACGIH) 20 ppm TWA
AEL * (DUPONT) 20 ppm 8 & 12 hr. TWA
 Skin designation

* AEL is DuPont's Acceptable Exposure Limit. Where governmentally imposed occupational exposure limits which are lower than the AEL are in effect, such limits shall take precedence.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Form : liquid

Material Safety Data Sheet



DuPont™ StoneTech® Professional Enhancer

Version 2.0

Revision Date 08/31/2010

Ref. 130000031663

Color : milky, white
Odor : ether-like
pH : 4.5
Boiling point : 100 °C (212 °F)
% Volatile : 85 - 95 %
Specific Gravity : 1.0
Water solubility : soluble

SECTION 10. STABILITY AND REACTIVITY

Stability : Stable under normal conditions.
Conditions to avoid : To avoid thermal decomposition, do not overheat.
Hazardous decomposition products : , Carbon dioxide , Carbon monoxide, Hydrogen fluoride
Incompletely burned carbon products
Other hazardous decomposition products may be formed.

SECTION 11. TOXICOLOGICAL INFORMATION

2-Butoxyethanol
Dermal LD50 : 210 mg/kg , guinea pig
Dermal : rabbit
Bloody urine
Oral LD50 : 300 mg/kg , rabbit
Oral : rat
Abnormal decrease in number of red blood cells
Inhalation LC50 : 2.21 mg/l , rat
Inhalation : rat
Abnormal decrease in number of red blood cells
Skin irritation : Skin irritation, multiple species
Eye irritation : animals (unspecified species)



DuPont™ StoneTech® Professional Enhancer

Version 2.0

Revision Date 08/31/2010

Ref. 130000031663

irritant

- Skin sensitization : animals (unspecified species)
Not a skin sensitizer.
- Repeated dose toxicity : Oral
animals (unspecified species)
Liver effects, Kidney effects, Bloody urine
- Carcinogenicity : An increased incidence of tumours was observed in some laboratory
animals but not in others.
- Mutagenicity : Tests on bacterial or mammalian cell cultures did not show mutagenic
effects.
- Reproductive toxicity : Animal testing showed effects on reproduction at levels equal to or
above those causing parental toxicity.
- Teratogenicity : Animal testing showed effects on embryo-foetal development at levels
equal to or above those causing maternal toxicity.
- Fluorinated Acrylic Copolymer
- Dermal ALD : > 5,000 mg/kg , rabbit
- Oral ALD : > 11,000 mg/kg , rat
- Inhalation 4 h ALC : >1600 mg/m3, rat
- Skin irritation : No skin irritation, rabbit
- Eye irritation : slight irritation, rabbit
- Skin sensitization : Did not cause sensitization on laboratory animals., mice
- Mutagenicity : Tests on bacterial or mammalian cell cultures did not show mutagenic
effects.

SECTION 12. ECOLOGICAL INFORMATION

Aquatic Toxicity

2-Butoxyethanol

Material Safety Data Sheet



DuPont™ StoneTech® Professional Enhancer

Version 2.0

Revision Date 08/31/2010

Ref. 130000031663

96 h LC50 : Fish (unspecified species) 1,490 mg/l

Fluorinated Acrylic Copolymer
96 h LC50 : Oncorhynchus mykiss (rainbow trout) 32 mg/l

96 h LC50 : Pimephales promelas (fathead minnow) 50 - 500 mg/l

72 h EC50 : Scenedesmus capricornutum (fresh water algae) 1.17 mg/l

48 h EC50 : Daphnia magna (Water flea) > 100 mg/l

Environmental Fate

Fluorinated Acrylic Copolymer
Biodegradability : Product is not expected to be biodegradable.

SECTION 13. DISPOSAL CONSIDERATIONS

Waste Disposal : In accordance with local and national regulations.

SECTION 14. TRANSPORT INFORMATION

Not classified as dangerous in the meaning of transport regulations.

SECTION 15. REGULATORY INFORMATION

SARA 313 Regulated
Chemical(s) : 2-Butoxyethanol

CERCLA Reportable
Quantity : 53 lbs
Based on the percentage composition of this chemical in the product.:
2-Butoxyethanol

PA Right to Know : Substances on the Pennsylvania Hazardous Substances List present at



DuPont™ StoneTech® Professional Enhancer

Version 2.0

Revision Date 08/31/2010

Ref. 130000031663

Regulated Chemical(s) a concentration of 1% or more (0.01% for Special Hazardous Substances): 2-Butoxyethanol

NJ Right to Know : Substances on the New Jersey Workplace Hazardous Substance List
Regulated Chemical(s) present at a concentration of 1% or more (0.1% for substances identified as carcinogens, mutagens or teratogens): 2-Butoxyethanol

SECTION 16. OTHER INFORMATION

DuPont™ and Stone Tech® are registered trademarks or trademarks of E. I. du Pont de Nemours and Company or its affiliates. The DuPont Oval Logo is a registered trademark of E.I. du Pont de Nemours and Company.

Contact person : MSDS Coordinator, DuPont Chemicals and Fluoroproducts, Wilmington, DE 19898, (800) 441-7515

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.

Significant change from previous version is denoted with a double bar.