



DuPont™ StoneTech® Professional Impregnator Pro® Sealer

Version 2.1

Revision Date 05/19/2010

Ref. 130000027527

This SDS adheres to the standards and regulatory requirements of the United States and may not meet the regulatory requirements in other countries.

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product name : DuPont™ StoneTech® Professional Impregnator Pro® Sealer
 MSDS Number : 130000027527

Manufacturer : DuPont
 1007 Market Street
 Wilmington, DE 19898

Product Information : 1-800-441-7515 (outside the U.S. 1-302-774-1000)
 Medical Emergency : 1-800-441-3637 (outside the U.S. 1-302-774-1139)
 Transport Emergency : CHEMTREC: 1-800-424-9300 (outside the U.S. 1-703-527-3887)

SECTION 2. HAZARDS IDENTIFICATION

Potential Health Effects

Skin : May cause skin irritation. Prolonged or repeated skin contact with liquid may cause defatting resulting in drying, redness and possible blistering.

Eyes : May cause: Eye irritation, tearing, Blurred vision, Discomfort.

Inhalation : Inhalation of aerosol or fine spray mist may cause serious respiratory problems. Inhalation of decomposition products in high concentration may cause shortness of breath (lung oedema)., Causes respiratory tract irritation., Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness..

Ingestion

Naphtha (petroleum), hydrotreated heavy (<0.1% benzene) : Aspiration hazard if swallowed - can enter lungs and cause damage.

n-Butyl acetate : Effects due to ingestion may include: narcosis

Repeated exposure



DuPont™ StoneTech® Professional Impregnator Pro® Sealer

Version 2.1

Revision Date 05/19/2010

Ref. 130000027527

Naphtha (petroleum), hydrotreated heavy (<0.1% benzene) : Adverse effects from repeated inhalation may include: Central nervous system effects Altered behaviour Kidney effects

n-Butyl acetate : Adverse effects from repeated ingestion may include: Kidney effects
Adverse effects from repeated inhalation may include: Respiratory tract irritation Liver effects

Target Organs

n-Butyl acetate : Liver Kidney Respiratory Tract Stomach Central nervous system

Carcinogenicity

None of the components present in this material at concentrations equal to or greater than 0.1% are listed by IARC, NTP, or OSHA, as a carcinogen.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Component	CAS-No.	Concentration
Naphtha (petroleum), hydrotreated heavy (<0.1% benzene)	64742-48-9	90 - 98 %
n-Butyl acetate	123-86-4	1 - 5 %
Fluorinated Acrylic Copolymer		1 - 5 %

SECTION 4. FIRST AID MEASURES

Skin contact : Wash off immediately with soap and plenty of water. Wash contaminated clothing before re-use.



DuPont™ StoneTech® Professional Impregnator Pro® Sealer

Version 2.1

Revision Date 05/19/2010

Ref. 130000027527

- Eye contact : Rinse immediately with plenty of water for at least 15 minutes. Seek medical advice.
- Inhalation : Move to fresh air. Oxygen or artificial respiration if needed. Symptoms may be delayed. Call a physician immediately.
- Ingestion : Call a physician or poison control centre immediately. If swallowed, DO NOT induce vomiting unless directed to do so by medical personnel. Never give anything by mouth to an unconscious person.
- General advice : When symptoms persist or in all cases of doubt seek medical advice.

SECTION 5. FIRE-FIGHTING MEASURES

- Flammable Properties
 - Flash point : 49 °C (120 °F) closed cup
- Fire and Explosion Hazard : Combustible
Hazardous decomposition products formed under fire conditions. Hazardous combustion products Hydrogen fluoride Carbon dioxide (CO2) Carbon monoxide Other hazardous decomposition products may be formed.
- Suitable extinguishing media : Water mist, Foam, Dry chemical, Carbon dioxide (CO2)
- Firefighting Instructions : Wear self contained breathing apparatus for fire fighting if necessary. Evacuate personnel to safe areas. Cool containers / tanks with water spray. Do not allow run-off from fire fighting to enter drains or water courses.

SECTION 6. ACCIDENTAL RELEASE MEASURES

NOTE: Review FIRE FIGHTING MEASURES and HANDLING (PERSONNEL) sections before proceeding with clean-up. Use appropriate PERSONAL PROTECTIVE EQUIPMENT during clean-up.

- Safeguards (Personnel) : Evacuate personnel to safe areas. Use personal protective equipment. Ventilate the area.
- Spill Cleanup : Remove all sources of ignition. Use only non-sparking tools. Dam up. Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Pick up and transfer to properly labelled containers.



DuPont™ StoneTech® Professional Impregnator Pro® Sealer

Version 2.1

Revision Date 05/19/2010

Ref. 130000027527

Accidental Release Measures : Do not discharge to streams, ponds, lakes or sewers. Avoid subsoil penetration.

SECTION 7. HANDLING AND STORAGE

- Handling (Personnel) : Do not use sparking tools. Avoid formation of respirable particles. Do not breathe vapours or spray mist. Avoid contact with skin, eyes and clothing. Wash hands before breaks and immediately after handling the product. Wash contaminated clothing before re-use.
- Handling (Physical Aspects) : Vapours may form explosive mixtures with air. Keep away from open flames, hot surfaces and sources of ignition. To avoid thermal decomposition, do not overheat. Thermal decomposition can lead to release of irritating gases and vapours.
- Storage : Keep containers tightly closed in a dry, cool and well-ventilated place. Grounding and elimination of the static charge is recommended. Store in accordance with National Fire Protection Association recommendations.

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

- Engineering controls : Use of non-sparking and explosion-proof equipment may be necessary depending on type of operation. Use only in area provided with appropriate exhaust ventilation. Use appropriate workplace ventilation to remove fumes that may be released on heating. Use an airless flow type of spray applicator. Keep spraying pressure below 60 psi.
- Personal protective equipment
 - Respiratory protection : In case of mist, spray or aerosol exposure wear suitable personal respiratory protection and protective suit.
 - Hand protection : Additional protection: Impervious gloves
 - Eye protection : Wear safety glasses or coverall chemical splash goggles.
 - Skin and body protection : Lightweight protective clothing

Exposure Guidelines

Exposure Limit Values

Naphtha (petroleum), hydrotreated heavy (<0.1% benzene)



DuPont™ StoneTech® Professional Impregnator Pro® Sealer

Version 2.1

Revision Date 05/19/2010

Ref. 130000027527

AEL *	(DUPONT)	100 ppm	8 hr. TWA
n-Butyl acetate PEL:	(OSHA)	150 ppm	710 mg/m3 8 hr. TWA
TLV	(ACGIH)	150 ppm	TWA
TLV	(ACGIH)	200 ppm	STEL

* AEL is DuPont's Acceptable Exposure Limit. Where governmentally imposed occupational exposure limits which are lower than the AEL are in effect, such limits shall take precedence.

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Form	: liquid
Color	: colourless
Odor	: mild, hydrocarbon-like
Boiling point/boiling range	: 171 °C (340 °F)
% Volatile	: > 95 %
Specific Gravity	: 0.8 at 25 °C (77 °F)
Water solubility	: negligible

SECTION 10. STABILITY AND REACTIVITY

Stability	: Stable under normal conditions.
Conditions to avoid	: To avoid thermal decomposition, do not overheat.
Hazardous decomposition products	: Incompletely burned carbon products , Carbon dioxide , Carbon monoxide, Hydrogen fluoride Other hazardous decomposition products may be formed.

SECTION 11. TOXICOLOGICAL INFORMATION

Naphtha (petroleum), hydrotreated heavy (<0.1% benzene)
Dermal LD50 : > 3,200 mg/kg , rabbit



DuPont™ StoneTech® Professional Impregnator Pro® Sealer

Version 2.1

Revision Date 05/19/2010

Ref. 130000027527

Oral LD50	:	> 5,000 mg/kg , rat
Inhalation	:	An LC50/inhalation/4h/rat could not be determined because no mortality of rats was observed at the maximum achievable concentration.
Skin irritation	:	Mild skin irritation, rabbit
Eye irritation	:	slight irritation, rabbit The toxicological data has been taken from products of similar composition.
Skin sensitization	:	Did not cause sensitization on laboratory animals., guinea pig
Repeated dose toxicity	:	human Target Organs: Central nervous system Chronic exposure damages the brain and the central nervous system.
Carcinogenicity	:	Overall weight of evidence indicates that the substance is not carcinogenic.
Mutagenicity	:	Tests on bacterial or mammalian cell cultures did not show mutagenic effects. Did not cause genetic damage in animals.
Reproductive toxicity	:	Evidence suggests the substance is not a reproductive toxin in animals.
Teratogenicity	:	Evidence suggests the substance is not a developmental toxin in animals.
n-Butyl acetate		
Dermal LD50	:	> 17,652 mg/kg , rabbit
Oral LD50	:	14,130 mg/kg , rat
Oral	:	rabbit narcosis
Inhalation 4 h LC50	:	44 mg/l , rat Target Organs: Central nervous system



DuPont™ StoneTech® Professional Impregnator Pro® Sealer

Version 2.1

Revision Date 05/19/2010

Ref. 130000027527

		narcosis
Inhalation	:	mouse Altered behaviour
Skin irritation	:	Mild skin irritation, rabbit
Eye irritation	:	Mild eye irritation, rabbit
Skin sensitization	:	human Not a skin sensitizer.
Repeated dose toxicity	:	Oral rat Kidney damage
		Inhalation rat Respiratory tract irritation, Reduced body weight gain
		Inhalation rabbit Increased liver enzyme levels in serum
Mutagenicity	:	Evidence suggests this substance does not cause genetic damage in animals.
Reproductive toxicity	:	No toxicity to reproduction
Teratogenicity	:	Animal testing showed effects on embryo-foetal development at levels equal to or above those causing maternal toxicity.
Fluorinated Acrylic Copolymer		
Oral LD50	:	> 2,000 mg/kg , rat
Inhalation 4 h ALC	:	> 105.8 mg/m3 , rat
Skin irritation	:	rabbit slight irritation
Eye irritation	:	rabbit Eye irritation



DuPont™ StoneTech® Professional Impregnator Pro® Sealer

Version 2.1

Revision Date 05/19/2010

Ref. 130000027527

Skin sensitization : guinea pig
Did not cause sensitization on laboratory animals.

SECTION 12. ECOLOGICAL INFORMATION

Aquatic Toxicity

Naphtha (petroleum), hydrotreated heavy (<0.1% benzene)
96 h LC50 : Pimephales promelas (fathead minnow) > 2,200 mg/l

n-Butyl acetate
96 h LC50 : Pimephales promelas (fathead minnow) 19 mg/l

Fluorinated Acrylic Copolymer
48 h EC50 : Daphnia 56 mg/l

Environmental Fate

Fluorinated Acrylic Copolymer
Biodegradability : Expected to be biodegradable

Bioaccumulation : Bioaccumulation is unlikely.

SECTION 13. DISPOSAL CONSIDERATIONS

Waste Disposal : In accordance with local and national regulations.

SECTION 14. TRANSPORT INFORMATION

DOT UN-Number : 3295

Proper shipping name : Hydrocarbons, liquid, n.o.s.

Class : 3

Packing group : III

Labelling No. : 3


DuPont™ StoneTech® Professional Impregnator Pro® Sealer

Version 2.1

Revision Date 05/19/2010

Ref. 130000027527

IATA_C	UN-Number	: 3295
	Proper shipping name	: Hydrocarbons, liquid, n.o.s.
	Class	: 3
	Packing group	: III
	Labelling No.	: 3
IMDG	UN-Number	: 3295
	Proper shipping name	: Hydrocarbons, liquid, n.o.s.
	Class	: 3
	Packing group	: III
	Labelling No.	: 3

SECTION 15. REGULATORY INFORMATION

SARA 313 Regulated Chemical(s)	: SARA 313: This material does not contain any chemical components with known CAS numbers that exceed the threshold (de minimis) reporting levels established by SARA Title III, Section 313.
California Prop. 65	: Chemicals known to the State of California to cause cancer, birth defects or any other harm: none known
PA Right to Know Regulated Chemical(s)	: Substances on the Pennsylvania Hazardous Substances List present at a concentration of 1% or more (0.01% for Special Hazardous Substances): n-Butyl acetate
NJ Right to Know Regulated Chemical(s)	: Substances on the New Jersey Workplace Hazardous Substance List present at a concentration of 1% or more (0.1% for substances identified as carcinogens, mutagens or teratogens): n-Butyl acetate

Material Safety Data Sheet



DuPont™ StoneTech® Professional Impregnator Pro® Sealer

Version 2.1

Revision Date 05/19/2010

Ref. 130000027527

SECTION 16. OTHER INFORMATION

DuPont™ and StoneTech® are registered trademarks or trademarks of E. I. du Pont de Nemours and Company or its affiliates. The DuPont Oval Logo is a registered trademark of E.I. du Pont de Nemours and Company.

Contact person : MSDS Coordinator, DuPont Chemicals and Fluoroproducts, Wilmington, DE
19898, (800) 441-7515

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text. Significant change from previous version is denoted with a double bar.