



ANTHRACITE



BEIGE



GREIGE



GREY

LIMEWALK

Regularity Characteristics

Technical Features	Norms	Required Standards	Matte
Length & Width	ISO 10545-2	± 0,6%* ± 2,0 mm	Not Provided by Manufacturer
Thickness		± 5,0% ± 0,5 mm	Not Provided by Manufacturer
Straightness of Sides		± 0,5% ± 1,5 mm	Not Provided by Manufacturer
Rectangularity		± 0,5% ± 2,0 mm	Not Provided by Manufacturer
Surface Flatness		c.c. ± 0,75% e.c. ± 0,75% w ± 0,75%	Not Provided by Manufacturer

Structural Characteristics

Technical Features	Norms	Required Standards	Matte
Water Absorption	ISO 10545-3	≤ 0,5% 0,6 % max.	0,7%

Bulk Mechanical Characteristics

Technical Features	Norms	Required Standards	Matte
Breaking Strength	ISO 10545-4	S ≥ 1300 N	S ≥ 2000 N
Modulus of Rupture		R ≥ 35 N/mm ²	R ≥ 40 N/mm ²

Surface Mechanical Characteristics

Technical Features	Norms	Required Standards	Matte
Mohs Hardness	EN 101	≥ 6	7
Resistance to Deep Abrasion	ISO 10545-7		V

Thermal and Hygrometric Characteristics

Technical Features	Norms	Required Standards	Matte
Coefficient of Thermal Linear Expansion	ISO 10545-8	Test Method Available	Not Provided by Manufacturer
Thermal Shock Resistance	ISO 10545-9	Test Method Available	Not Provided by Manufacturer
Moisture Expansion	ISO 10545-10	Test Method Available	Not Provided by Manufacturer
Resistance to Frost	ISO 10545-12	Required	Not Provided by Manufacturer

Safety Characteristics

Technical Features	Norms	Required Standards	Matte
Dynamic Friction Coefficient	ANSI 137.1-2012 (D.C.O.F.)	≥ 0,42 WET	Not Provided by Manufacturer
Static Coefficient of Friction	ANSI A137.1-2012	≥ 0,42	Not Provided by Manufacturer
Non-Slip Classification	DIN 51130	Basing on the Environment or on the Working Area	R10
Resistance to Frost	DIN 51097	Basing on the Wet-Loaded Barefoot Areas	Not Provided by Manufacturer

Chemical Characteristics

Technical Features	Norms	Required Standards	Matte
Resistance to Household Chemicals and Swimming Pool Salts	ISO 10545-13	Class GB min.	GA
Resistance to low Concentrations of Acids and Alkalis		Test Method Available	GLA
Resistance to High Concentrations of Acids and Alkalis		Test Method Available	Not Provided by Manufacturer
Resistance to Staining	ISO 10545-14	Class 3 min.	5

Stacked Sizes (Nominal)

Dimensions	Available Colors
12x24" Field Tile	Anthracite, Beige, Greige, Grey
18x36" Field Tile	Anthracite, Beige, Greige, Grey
2x24" Bullnose	Anthracite, Beige, Greige, Grey
12x12" Mix Mosaic	Anthracite, Beige, Greige, Grey

Special Order Sizes* (Nominal)

Dimensions	Available Colors
60x60 - 24"x24" Field Tile 	Anthracite, Beige, Greige, Grey
60x60 - 24"x24" Field Tile 	Anthracite, Beige, Greige, Grey (Out)
45,5x91 - 18"x36 1/2" Field Tile 	Anthracite, Beige, Greige, Grey (Out)
30x60 - 12"x24" Stick Mosaic 	Anthracite, Beige, Greige, Grey

* 12 - 14 Week Lead Time. Some additional trim and decor pieces are available.

Recycled Content

 Not Provided By Manufacturer
--

Shade Variation Not Provided
By Manufacturer