








Smoke

TRACKS

⟨S



Structural Characteristics			
Technical Features	Norms	Required Standards	Matte
Water Absorption	ISO 10545-3	≤ 0,5%	Suitable For

Technical Features	Norms	Required Standards	Matte
Breaking Strength	150 10515 1	S ≥ 600 N	Suitable For
Modulus of Rupture	ISO 10545-4	R ≥ 15 N/mm²	Suitable For

Technical Features	Norms	Required Standards	Matte
Mohs Hardness	EN 101	≥ 6	Not Provided by Manufacturer
Resistance to Deep Abrasion	ISO 10545-6	≤ 175 mm³	Not Provided by Manufacturer

Technical Features	Norms	Required Standards	Matte
Coefficient of Thermal Linear Expansion	ISO 10545-8	Test Method Available	Not Provided by Manufacturer
Resistance to Crazing	ISO 10545-11	Test Method Available	Resistant
Resistance to Frost	ISO 10545-12	Required	Not Provided by Manufacturer

Technical Features	Norms	Required Standards	Matte
Dynamic Friction Coefficient	ANSI 137.1-2012 (D.C.O.F.)	≥ 0,42 WET	≥ 0,42 WET
Static Coefficient of Friction	ASTM C 1028 (S.C.O.F.)	Slip Resistant (≥ 0,60)	≥ 0,60 DRY ≥ 0,60 WET
Non-Slip Classification	DIN 51130	Basing on the Environment or on the Working Area	R9



Technical Features	Norms	Required Standards	Matte
Resistance to Household Chemicals and Swimming Pool Salts	ISO 10545-13	Class UB min.	UA
Resistance to low Concentrations of Acids and Alkalis		Manufacturer to State Classification	ULA
Resistance to High Concentrations of Acids and Alkalis		Test Method Available	UHA
Resistance to Staining	ISO 10545-14	Test Method Available	Cleanable

Dimensions	Available Colors
12"x24"x9mm Field Tile	Ivory, Grey, Sand, Smoke
3.2"x18" Bullnose	Ivory, Grey, Sand, Smoke

Dimensions	Available Colors
60x60 - 24"x24" Field Tile	Ivory, Grey, Sand, Smoke
45x45 - 18"x18" Field Tile	Ivory, Grey, Sand, Smoke
Décor	N/A
Gradino	N/A
Scalino	N/A
Scalino Angolare	N/A
15 List.P	N/A
15 A/Est P	N/A
Mosaic	N/A

* 12 - 14 Week Lead Time

