

ZERO DESIGN




Sabbia Salar White



Sabbia Gobi Grey



Sabbia Thar Beige



V3 Moderate Variation

Chemical Characteristics

Technical Features	Norms	Required Standards	Value
Resistance to Household Chemicals and Swimming Pool Salts	ISO 10545-13	Not Specified by Manufacturer	GA
Resistance to Low Concentrations of Acids and Alkalies		Not Specified by Manufacturer	GLA
Resistance to High Concentrations of Acids and Alkalies		Not Specified by Manufacturer	GLA
Resistance to Staining	ISO 10545-14	Not Specified by Manufacturer	5

Stocked Sizes (Nominal)

Dimensions	Available Colors
12"x24"x10mm Field Tile	Salar White, Thar Beige, Gobi Grey (Sabbia)
24"x48"x10mm Field Tile	Salar White, Thar Beige, Gobi Grey (Sabbia)
3"x24" Bullnose	Salar White, Thar Beige, Gobi Grey (Sabbia)
1"x1" on 12"x12" Mosaico	Salar White, Thar Beige, Gobi Grey (Sabbia)

Special Order Sizes* (Nominal)

Dimensions	Available Colors
30x60 - 11 1/8"x23 1/8" Field Tile	Salar White, Thar Beige, Gobi Grey (Sabbia Lappato) Bolivian White, Indian Beige, Asian Grey (Pietra Natural & Lappato)
45x90 - 17 1/8"x35 1/8" Field Tile	Salar White, Thar Beige, Gobi Grey (Sabbia Natural & Lappato) Bolivian White, Indian Beige, Asian Grey (Pietra Natural & Lappato)
60x120 - 23 1/8"x47 1/8" Field Tile	Salar White, Thar Beige, Gobi Grey (Sabbia Lappato) Bolivian White, Indian Beige, Asian Grey (Pietra Natural & Lappato)
30x30 - 11 1/8"x11 1/8" 4"x4" Mosaico	Bolivian White, Indian Beige, Asian Grey (Pietra Natural)
30x30 - 11 1/8"x11 1/8" 2"x2" Mosaico	Salar White, Thar Beige, Gobi Grey (Sabbia Natural) Bolivian White, Indian Beige, Asian Grey (Pietra Natural)
30x30 - 11 1/8"x11 1/8" 1"x1" Mosaico	Bolivian White, Indian Beige, Asian Grey (Pietra Natural)

* 12 - 14 Week Lead Time. Some additional trim and decor pieces are available.

Recycled Content

20% - 12"x24"

Regularity Characteristics

Technical Features	Norms	Required Standards	Value
Length & Width	ISO 10545-2	Not Specified by Manufacturer	± 0,26% ± 1,5mm
Thickness		Not Specified by Manufacturer	Not Specified by Manufacturer
Straightness of Sides		Not Specified by Manufacturer	Not Specified by Manufacturer
Rectangularity		± 0,40%	± 0,25% (max ± 0,05 in-size ≤ 60cm) (max ± 0,07 in-size > 60cm)
Surface Flatness		Not Specified by Manufacturer	Not Specified by Manufacturer

Structural Characteristics

Technical Features	Norms	Required Standards	Value
Water Absorption	ISO 10545-3	≤ 0,5 %	Suitable For

Bulk Mechanical Characteristics

Technical Features	Norms	Required Standards	Value
Breaking Strength	ISO 10545-4	Not Specified by Manufacturer	≥ 2000 N
Modulus of Rupture		Not Specified by Manufacturer	≥ 50 N/mm ²

Surface Mechanical Characteristics

Technical Features	Norms	Required Standards	Value
Mohs Hardness	EN 101	Not Specified by Manufacturer	Not Specified by Manufacturer
Resistance to Deep Abrasion	ISO 10545-6	≤ 175 mm ³	≤ 150 mm ³

Thermal and Hygrometric Characteristics

Technical Features	Norms	Required Standards	Value
Coefficient of Thermal Linear Expansion	ISO 10545-8	Not Specified by Manufacturer	Not Specified by Manufacturer
Thermal Shock Resistance	ISO 10545-9	Not Specified by Manufacturer	Not Specified by Manufacturer
Resistance to Frost	ISO 10545-12	Required	Resistant

Safety Characteristics

Technical Features	Norms	Required Standards	Sabbia	Pietra
Dynamic Coefficient of Friction	ANSI 137.1-2012 (D.C.O.F.)	≥ 0,42 WET	Nat. ≥ 0,85 DRY ≥ 0,77 WET	Nat. ≥ 0,85 DRY ≥ 0,77 WET
Slip Resistance	DIN 51097	Not Specified by Manufacturer	B (A+B) Nat. A Lapp.	B (A+B) Nat. A Lapp.
Non-Slip Classification	DIN 51130	Not Specified by Manufacturer	R10 Nat. - Lapp.	R10 Nat. - Lapp.